



Development of flash flood warning system for road users in Port Harcourt metropolis

Mokwe Uju Vivian¹, Omijeh Bourdillon O¹, Eludoyin olatunde S², Okeke Remigius Obinna³

¹ Centre for Information and Telecommunication Engineering, University of Port Harcourt, Rivers State, Nigeria

² Department of Geography and Environmental Management, University of Port Harcourt, Rivers State, Nigeria

³ Department of Electrical/Electronic Engineering, University of Port Harcourt, Rivers State, Nigeria

Abstract

Flash floods, which combine the destructive power of a flood with exceptionally rapid speeds, are the most dangerous kind of flooding. The goal of this project is to develop a flash flood warning system that uses a mobile device to detect floods and immediately alert drivers via Rumuigbo, Port Harcourt's Nkpolu Road. Along with rainfall data gathered from the Nigeria Meteorological Agency (NIMET), soil samples obtained from Nkpolu Road were brought to the lab and analysed. The measurement device was built based on the analysis of the soil sample and rainfall data. The system incorporates the following components: the Arduino microcontroller, the SHT20 soil temperature/humidity sensor, the DFRobot gravity pH sensor, the SIM900L data transfer module, and the HC-SR04 ultrasonic sensor. The study indicates that the soil types on Nkpolu Road are sandy loam and loamy sand, and that July through September is typically the wettest month in terms of rainfall intensity. According to the analysis's findings, the road frequently saw flash floods as a result of the intense downpour and the soil's poor water-holding ability. Consequently, there was a lot of water runoff, especially in July and September. The system on Nkpolu Road was designed to send out warning messages via a mobile device every six minutes and to identify flash floods when it rained. When the rain started to come down, the alerts would progress from saying "no flooding" to "minor flooding," "moderate flooding," and eventually "severe flooding." They would then send out warnings in real time as soon as each degree of flooding was determined. The warning that day that it rained was "no flooding". When it didn't rain at all, no warning signal was sent. When the Nkpolu Road floods, this technology helps drivers avoid the area and instantly switch to another route that is open.

Keywords: Flood, flooding, flash flooding, river state Nigeria, flash flooding warning system, mobile device, rainfall

Introduction

The globe is in danger due to numerous environmental issues (Christopherson, 1997; Oyegbile, O., 2008). Kolafe *et al.* (2015) state that flooding is thought to be the most catastrophic natural disaster on Earth. Flooding happens when an excessive amount of water rushes over normally dry terrain (Djimesah *et al.*, 2018). This can happen when rainfall exceeds the soil's capacity to hold it down (Nwachukwu *et al.*, 2018). As stated by Peduzzi *et al.* (2009), "the rate of flood occurrence in recent times has been unprecedented," with over 800 million people living in flood-prone areas and 70 million people annually exposed to floods. According to Rentschler and Salhab, flood disasters happen once every 100 years, and at those times, 14.7 billion people, or 19% of the world's population, are directly exposed to serious risks. Destructive floods have been a major calamity ever since the dawn of humanity. Usually located along to waterways, they have towns that are in danger of being destroyed. Since floods are a natural event, they happen frequently. Despite all attempts at flood management, the threat of flooding has not been totally eliminated, and it is unlikely that it ever will be, as flood defenses sometimes fall short of offering comprehensive protection. The average annual damage due to flooding has risen to several billion US dollars worldwide. Certain recent floods have shattered records for both total material losses (social and economic qualities) and absolute record stages (geophysical aspects) when compared to floods during the period of observational data. Each year, floods claim thousands of lives. There are several kinds of floods, each

With special traits and a long history of precautionary actions taken by people. There are river floods that reach a continental scale (produced by rainfall, snowmelt, or a combination of the two), debris flows, floods in deltas threatened by storm surges, ice jam floods, and dam breach floods. The world's expanding urbanization, the expansion of settlements into flood-prone areas, and our over-reliance on the protection offered by flood control projects like levees and reservoirs are all contributing factors to the potential for flood damage. Small and medium-sized floods are often protected from by dikes; that is, the frequency of floods in this range is declining. However, the losses in a levee-protected landscape surpass those in a natural one when a disastrously large flood occurs and the dikes fail. Due to their flatness, fertile soil, and close proximity to water, flood plains—which are also prone to development—are areas where anthropopressure produces a desire to consume more land. Other factors contributing to an increased danger of flooding include a rise in the percentage of impermeable land, deforestation, and improvements made to channels, such as straightening water courses. Overall, there is an increase in the runoff coefficient, a quicker and higher hydrograph peak (the system's reaction to heavy precipitation), and a faster rate of water, sediment, and other material erosion and movement. Development has spread to steep slopes in mountainous areas that are vulnerable to debris flows and landslides. The issue is getting worse in steep places as a result of road construction, residential area development, and deforestation. Numerous catastrophic floods have occurred recently throughout the world are discussed in further detail in this contribution.

There are five different types of floods, according to the National Severe Storms Laboratory. These consist of:

1. River Flood
2. Coastal Flood
3. Storm Surge
4. Inland Flooding
5. Flash Flood

The foregoing list should have made it clear that flooding can occur anywhere, both inland and along the coast.

River Flooding

When water levels rise above the top of river banks, a river flood happens. It is possible for any river or stream channel to flood. This covers all waterways, from little streams to the biggest rivers on Earth.

River Flooding Causes

There are four main causes of river flooding. These are:

1. Excessive rainfall resulting from land falling tropical cyclone systems
2. Prolonged spans of time with persistent thunderstorms over the same region
3. Together, snowmelt and rainfall
4. Ice jam

Floods in rivers can occur quickly or gradually. Smaller rivers, rivers with steep valleys, rivers that flow over impermeable terrain for a significant portion of their length, and typically dry channels are more likely to experience sudden river flooding occurrences. Low-rising river floods, on the other hand, usually happen in big rivers with big catchment basins. Any area of land where precipitation gathers and flows off into a shared outlet is known as a catchment area.

Coastal Flood

The inundation of normally dry land regions near the coast with seawater is known as a coastal flood.

Causes of Coastal Flooding

A combination of strong winds, barometric pressure, and sea tidal surges usually causes coastal flooding. Usually, storms at sea produce these conditions, such as:

1. Storms in the tropics
2. Big Wave
3. More tides than usual

Storm Surge

Storm surge flooding is another kind of flooding that is frequently connected to coastal flooding.

An unusual rise in the water level in coastal locations above and beyond the typical astronomical tide is known as storm surge.

Causes of Storm Surge

Weather-related storms that produce higher-than-normal tides along the coast are always the cause of storm surge. This surge is the result of three storm components. What they are is:

1. The Wind
2. Ocean Waves
3. Lowered atmospheric pressure

Flooding that occurs from storm surge is very dangerous. It is capable of simultaneously flooding vast coastal areas.

Furthermore, it might soon result in flooding. Storm surges that coincide with high tides result in extremely heavy floods. Storm tides could get as high as twenty feet as a result of this! Storm surge is the most hazardous feature of every tropical system, meteorologists emphasize again. It is the most dangerous thing for people's lives and belongings.

Inland Flooding

Inland flooding is referred to as urban flooding by certain organizations. Another kind of inland flood is a flash flood. Any flooding that happens inland, away from the shore, is referred to as an inland flood. Storm surge and coastal flooding are therefore not considered inland floods.

Causes of Inland Flooding

Inland floods are nearly invariably caused by rainfall. Inland flooding is caused by rain in two ways. It might occur as a result of a brief but heavy downpour or as a result of consistent rain over several days. Inland floods are also caused by snowmelt, however rainfall is a more frequent culprit. Inland flooding can also occur when dams, ice, or debris obstruct waterways. Urban areas are frequently more vulnerable to inland floods due to the lack of outlets for the water to escape. The following urban characteristics have the potential to either cause or worsen inland flooding:

1. Paved streets and roads
2. Low-volume drainage apparatus
3. Dense structures
4. Insufficient green space

Flash Flood

One of the most catastrophic kinds of flooding is called a flash flood, and it usually results from very heavy rain falling quickly (NWS, 1995). Water released from the rain in six hours could not be absorbed by the soil due to the little duration and high intensity of the rain. The inability of the canals to drain this runoff, depending on the condition and size of the basin, could result in flooding that could be disastrous (Grunfest, 1998; Messner and Meyer, 2015). Scholars define flash floods in a number of ways, such as storm-driven phenomena or hydro-meteorological events. When everything is taken into account, a flash flood is defined as an exceptionally strong downpour that is followed by six hours of abrupt, catastrophic, and destruction (Lóczy, 2010). River flooding has historically caused the most damage from floods, but in recent years, it appears that attention has shifted to flash flooding due to its clear destructiveness, abruptness, unpredictability, and frequency. Given the aforementioned, it is imperative that flash flood hazard assessment be approached differently with respect to method, data, and processes because of topographic and general factors (Czigány *et al.*, 2010; Zhang *et al.*, 2001). Flash floods are always associated with other forms of flooding; they never happen in isolation. It's possible for one to trigger the other, in which case both might work together. Flash floods may cause landslides, river flooding, and other related but unanticipated phenomena (Iverson, 1997). Rainfall that triggers a flash flood is typically fairly strong, able to swiftly wet the surrounding ground, and able to carry the majority of objects with it as it flows off (Kofo, 2012). The short duration of a storm occurrence causes the water released

from the heavy rain to cover the land so quickly that the channels and basins cannot accommodate the large volume of water within the brief period of time. Furthermore, it might raise the stream's level to the point where the rushing water back upstream floods the surrounding area (Creutin and Borga, 2003; Collier, 2007). Flash floods are characterized by the destruction of highways, bridges, culverts, and other physical structures due to their quick movement and the weight of their load. Farmlands are submerged in water and debris during floods, which kills crops and other vegetation. It also releases hazardous chemicals from flooded chemical industries and sewage from vulnerable septic tanks. Given that the discharged water may contain animal excrement, chemical emissions, and faeces, public health issues could develop in addition to the spread of several diseases caused by the release of different pathogens (Kofo, 2012; Cutter, 1996). A flash flood is the most frequent and damaging type of flood. Flash floods can happen anywhere from a few minutes to several hours following a period of intense rain or an unplanned dam breakdown (NOAA, 1992). Experts say that after a significant downpour, flash floods usually occur six hours later. It happens in urban areas, along water channels, and in steep terrain and is linked to little warning (USDA, 2010). Furthermore, metropolitan centers were severely harmed by flash floods that happened in dry areas without stream courses. The extent of damage depends on how close the area is to the river channel. Stated differently, the effects of flash floods diminish with greater distance. The flash flood disaster was made worse by impervious surfaces and an inadequate drainage infrastructure (Menne and Murray, 2013; Mohammed, Worku, and Sterk, 2012). Urbanization results in impermeable surfaces because of the construction of roads, buildings, bridges, and recreational areas, all of which hasten runoff.

Causes of Flash Floods

Numerous factors can lead to flash floods. The majority of flash floods occur during brief but intense thunderstorms that produce a lot of rain in as little as six hours. Two essential components are needed to assess the likelihood of flash flooding:

1. Rate of rainfall
2. Duration of rainfall

Flash floods can also occur as a result of levee failure, dam failure, or the large-scale discharge of water from an ice jam.

Dangers of Flash Floods

The force of flash floods is immense. They are capable of uprooting trees, toppling boulders, demolishing bridges, and scouring new paths. Violent floods that rip through city streets, riverbeds, and canyons, destroying everything in their path, are the hallmark of this type of flooding. Waves as high as thirty feet can submerge entire communities during flash floods. Another reason why flash flooding is so deadly is that it can happen suddenly and without warning. This is particularly true in cases where dams or levees break. The US National Weather Service suggests being aware of the flood hazard in your neighbourhood before a flash flooding storm happens. In addition, they recommend creating an emergency plan for your family or company in case of a flash flood.

Materials and methods

The following materials were used in the flash flood warning system:

1. **Arduino Mega 2560 Board:** The Arduino Mega 2560 is a microcontroller board with an ATmega2560 microcontroller at its core. It offers a large number of digital and analogue input/output pins, making it suitable for complex projects. It also offers the required computing power and interfaces to connect and control various sensors. The Arduino Mega will act as the system's brain.
2. **HC-SR04 Ultrasonic Sensor:** The HC-SR04 is an affordable and widely used ultrasonic sensor that measures distances by emitting ultrasonic waves and calculating the time it takes for the waves to bounce back. In our system, the HC-SR04 will be used to measure the water level in a particular area susceptible to flash floods.
3. **SIM900L GSM Module:** The SIM900L GSM module will be in charge of communicating the water level data obtained by the HC-SR04 sensor to a mobile device over the Global System for Mobile communication (GSM) network.
4. **DFRobot Gravity pH Sensor:** The DFRobot Gravity pH sensor, which measures a solution's acidity or alkalinity, can be used to analyze the pH levels of soil, revealing important details about the soil type.
5. **SHT20 Soil Temperature/Humidity Sensor:** The SHT20 sensor provides precise readings of soil temperature and humidity, which are essential for comprehending soil moisture content and the likelihood of flash floods.

System Architecture

The flash flood warning system architecture involves the following steps:

6. **Sensor Connections:** Connect the DFRobot Gravity pH sensor, HC-SR04 ultrasonic sensor, SMI900L and SHT20 soil temperature/humidity sensor to the Arduino Mega 2560 board. Ensure that the sensor pins are correctly connected to the appropriate digital or analog input pins on the Arduino board.
7. **Sensor Data Acquisition:** Use the appropriate libraries and code to read data from the HC-SR04 ultrasonic sensor, pH sensor and SHT20 sensor. The libraries provide functions to interface with the sensors and retrieve accurate measurements of water level, pH, temperature, and humidity.
8. **Power Supply:** 2000mAh Battery A reliable power supply is essential for the continuous operation of our flash flood warning system, especially in remote or flood-prone areas where the electrical grid may be unreliable. We employ a 2000mAh rechargeable battery to power the system. This high-capacity battery provides extended runtime, ensuring that the system remains operational even in the absence of grid power. Additionally, the system incorporates power-saving mechanisms to optimize battery life, such as sleep modes and low-power sensor operation.

9. **Data Processing and Analysis:** Process the sensor data obtained from the Arduino board. Use algorithms and calculations to analyze the collected data. Calculate soil moisture levels, pH values, and interpret them to determine soil types and assess the risk of flash floods.
10. **Visualization and Reporting:** Present the analyzed data in a user-friendly format for effective decision-making. Visualize the data using graphs, charts, or maps to highlight soil characteristics, flood risk levels, and soil type distributions. Generate reports or alerts for relevant stakeholders to take appropriate actions.

System Algorithm

Here is an algorithm for the flash flood warning system using the HC-SR04 sensor for water level measurement, SIM900L module for data transmission and DFRobot Gravity pH sensor and SHT20 Soil temperature/humidity sensor connected to the Arduino Mega 2560 board for soil measurement and analysis:

1. Initialize the System:
 - Set up the Arduino Mega 2560 board and ensure all necessary libraries and dependencies are installed.
 - Connect the HC-SR04 sensor, SIM900L module, DFRobot Gravity pH sensor, and SHT20 Soil temperature/humidity sensor to the appropriate pins of the Arduino Mega 2560 board.
2. Establish Communication with SIM900L Module:
 - Initialize the SIM900L module and establish a communication link between the Arduino Mega 2560 board and the SIM900L module.
 - Set up the necessary parameters for network connectivity (e.g., APN, username, password).
 - Ensure the SIM card is inserted correctly and has an active data plan.
3. Measure Water Level Using HC-SR04 Sensor:
 - Configure the HC-SR04 sensor by setting the appropriate digital input and output pins on the Arduino.
 - Trigger the sensor by sending a short pulse from the Trig pin and measure the time it takes for the ultrasonic wave to return to the Echo pin.
 - Convert the measured time to distance using the speed of sound in air.
 - Calculate and store the water level based on the distance measurement.
4. Measure Soil pH Using DFRobot Gravity pH Sensor:
 - Read the analog input from the DFRobot Gravity pH sensor using the Arduino's analog input pin.
 - Convert the analog reading to the corresponding pH value using calibration data.
 - Store the pH value in a variable for further analysis and transmission.
5. Measure Soil Temperature and Humidity Using SHT20 Sensor:
 - Retrieve temperature and humidity data from the SHT20 sensor using the appropriate libraries and functions.
 - Store the temperature and humidity values in separate variables for further analysis and transmission.

6. Synchronize Data using SIM900L Module:
 - Format the collected sensor data (water level, pH, temperature, humidity) into a suitable data structure or format for transmission.
7. Repeat Monitoring and Analysis Process:
 - Set a suitable time interval for continuous monitoring and data collection.
 - Repeat steps 3-6 at regular intervals to update the water level, pH, temperature, and humidity measurements.
8. Handle Exceptional Cases:
 - Implement error handling mechanisms for scenarios such as network connection failures, sensor malfunctions, or data transmission errors.
 - Include appropriate error messages or notifications to indicate any issues encountered during the monitoring process.
9. Implement Power Management:
 - Optimize power consumption by employing sleep modes or power-saving techniques when the system is idle or not actively monitoring.
 - Consider using external power sources or batteries to ensure continuous operation in remote locations.

Conclusion

- Monitor the system's performance and make necessary adjustments or improvements based on real-world observations and user feedback.

Methods of Data Collection

The following steps outline the data acquisition and processing procedures:

1. Program the Arduino to trigger the HC-SR04 sensor by sending a short pulse from the Trig pin. Measure the time it takes for the ultrasonic wave to return to the Echo pin. Convert this time to distance using the speed of sound in air. Repeat this process for multiple sensors at different heights to monitor water levels accurately.
2. Read the analog input from the DFRobot Gravity pH sensor using the Arduino's analog input pin. Convert the analog reading to the corresponding pH value using calibration data. Store the pH values along with the timestamp for further analysis and transmission.
3. Retrieve temperature and humidity data from the SHT20 sensor using the appropriate libraries and functions. Store the acquired data along with the timestamp for subsequent analysis and transmission.

Rainfall Data

Data on rainfall in Port Harcourt was made available by the Nigerian Meteorological Agency at the Port Harcourt International Airport for the 36-year period spanning from 1981 to 2016 and from 2014 to 2022. Data analysis was conducted to investigate variations in rainfall for varying intensities on a daily, monthly, and annual scale. The analysis focused on examining patterns, changes, and/or occurrences over the specified period and their correlation with the fast spreading flash floods that affected the entire city.

Methods of Data Analysis

Rainfall Analysis

Rainfall data analysis is required to comprehend an area's trend, volume, potential for discharge, and planning needs. The primary purposes of the analysis are to design and develop the best flood water control policy as well as to supply input data for a flood management system. The analysis of rainfall data aids civil engineers in designing dams, bridges, and other structures depending on the area's best, worst, and predicted rainfall situations. When designing, constructing, and maintaining buildings connected to flooding, it is important to understand both complex and basic concepts such as moving averages, return periods, probabilities, mean annual rainfall, range, standard deviation, skewness, and intensities (Herath and Ratnayake, 2004). Rainfall Amount Surface runoff, often known as flash flooding, happens quickly when rainfall intensity is so strong that it surpasses both the rate of evaporation and the rate of penetration into the soil. An increase in rainfall at a certain place raises the likelihood of a flood (Nyarko, 2002). Since the earth cannot absorb all of the water falling as rain so quickly, higher rainfall rates lead to more runoff. The Center for Hydrometeorology and Remote Sensing (CHRS) at the University of California provided rainfall intensity data for 2016. Elkhrachy (2015) notes that the CHRS uses neural network function classification/approximation processes to compute a rainfall estimate rate at each $0.25^\circ \times 0.25^\circ$ pixel of the infrared brightness temperature image provided by geostationary satellites.

Topography Analysis

This study will incorporate topography information into the analysis by obtaining accurate elevation and slope data. This can be obtained from the Shuttle Radar Topographic Mission (STRM) website and processed through the use of geoinformation techniques which involve remote sensing and Geographic Information System techniques. Analyze the topographic data to identify potential drainage patterns, flood-prone areas, and other relevant features that influence soil conditions and water movement.

Performance Evaluation

The flash flood warning system proposed in this chapter uses an HC-SR04 ultrasonic sensor and an Arduino MEGA 2560 microcontroller to measure water levels in real-time and trigger alerts when the water level exceeds a predefined threshold. In this chapter, the performance of the system in terms of accuracy, reliability, and response time are evaluated. Also, prediction capability of the system was also evaluated.

Accuracy

To evaluate the accuracy of the flash flood warning system, we compared the water level measurements obtained from the system with the water level measurements obtained from a manual water level gauge. The manual gauge was used as a reference to validate the accuracy of the system. The tests were conducted over a period of time, during which the water level on the road varied.

Reliability

The reliability of the system was evaluated by testing the system's ability to operate continuously over an extended period. The tests were conducted for a period of time, during which the system was left to operate continuously without any intervention.

Response Time

The response time of the system was evaluated by measuring the time taken for the system to detect a change in the water level and trigger an alert. The tests were conducted by manually raising the water level on the road and measuring the time taken for the system to trigger an alert.

Result

From the result gotten from rainfall analysis and soil analysis, it was decided that the flash flood warning system be deployed on Nkpolu road in Port Harcourt metropolis in September. In other to avoid false alarm the system would first monitor the moisture content of the soil, once it detects moisture it would start sending out warning alert.

Result of Analysis of Soil

Particle size distribution (PSD), moisture content, permeability, and texture class were examined in the laboratory for two soil samples from Nkpolu Road in the Port Harcourt Metropolis, designated S1 to S2. The analysis's conclusion is as follows:

Sample S1: East West Road, Nkpolu Junction. The results of the analysis of Sample S1 revealed that it contained 74.00% sand, 5.56% silt, and 20.44% clay, with a moisture content of 14.93% and a permeability of 2.4×10^{-3} cm/sec. Sandy loam (SL) was identified as the texture class.

Sample S2: East West Road, Nkpolu Junction. The results of the analysis of Sample S2 revealed that it contained 78.96% sand, 9.60% silt, and 11.44% clay, with a moisture content of 23.22% and a permeability of 2.8×10^{-3} cm/sec. It was concluded that the textural class was loamy sand (LS).

Rainfall Data

The study conducted in 2011 by Chiadikobi *et al.* states that rainfall in Port Harcourt peaks in July, August, and September, with August serving as a brief interlude. According to the study, Port Harcourt floods in reaction to rainfall, with the biggest floods occurring during periods of peak rainfall. The City always faces flooding between July and September of each year, mostly due to rains.

Soil Analysis

General information on the type, composition, moisture content, and permeability of the soil was revealed by two soil samples that were taken for analysis at Nkpolu Road in Port Harcourt. After both samples were analyzed, it was determined that one was sandy loam (SL) and the other was loamy sand (LS). The high percentage of sand (average over 80%), silt component (average 6%), and clay component (average over 13%), characterize loamy sand (LS). The majority of the time, loamy sand has a moderate moisture content of over 15% and an average permeability of $2.0 \text{ cm/sec} \times 10^{-3}$. Loamy soil permits water to pass through sometimes until the moisture content reaches its maximum and is no longer able to do so, resulting in flash floods. During the sampling phase, a single location for sandy loam (SL) soil samples was taken. The average percentage of sand in the soil is between 74% and 79%, the average percentage of silt is 4%, and the average percentage of clay is more than 19%. The sandy loam soil typically has an average moisture content of more than 12% and a permeability of roughly $1.7 \text{ cm/sec} \times 10^{-3}$. Floods are

possible because the sandy loam soil fills in quickly and lets little water through. The findings of the soil analysis revealed that all of the sand fractions were medium and fine in size. The percentage of soil that was retained on a sieve with a 2.00 mm mesh size ranged from 87.73 to 97.89%, and the particle size diameter was between 0.84 and 1.92 mm. The samples' average moisture content was medium, and their permeability values were typically very low in one and too low in the other. These characteristics contributed to the flash flood that was seen during the rainy season. This was in line with a 2011 study by Chiadikobi *et al.* that found that the aforementioned characteristics of soils make them more prone to floods. The primary causes of flash floods are heavy rains that come primarily between May and September each year. Because of the city's highly moist soil, which is less porous and readily filled to capacity, runoff from heavy rainfall occurs frequently, leading to flash floods. Because of the city of Port Harcourt's rugged terrain, the drainage system is extremely intricate. Because most of the city is constructed on average low to somewhat sloppy terrain, flash floods can be quite destructive in certain places while remaining mild and low in others. Residents of the city are at risk of flash floods during the rainy months due to the city's high precipitation rates, sloppy terrain in some areas, less permeable soil with a moderate to high moisture content, poor land use and land cover, and high drainage density.

Conclusion

According to Pratomato (2016), flash floods can be triggered either alone or in combination by intense rainfall, abrupt lake breaches, check dam collapses, and extremely steep terrain. Due to a number of issues with forecasting and the speed at which they inflict havoc, flash floods are particularly destructive and devastating floods that slow down and minimize emergency responses (Smith and Petley, 2009). Due to climate change variability, which produces rainstorms, snowmelt, glacial lake outbursts, and high intensity rainfall, flash floods are affecting people, wildlife, homes, and populations all over the world. These events lower living standards and result in significant economic loss as well as infrastructure damage (Ali *et al.*, 2016). Floods are the most frequent and well-known natural disaster, with virtually no chance of prevention or mitigation. Therefore, efforts to lessen their influence or impact on the human population are crucial (Ali *et al.*, 2016).

Protection, readiness, and prevention are the main objectives of flash flood warning systems in order to drastically reduce future flood-related expenses.

A warning system for flash floods is primarily designed to advise cars to stay off flooded roads in an effort to prevent or reduce casualties, property damage, and social disturbance. Their objective is also to promote deliberate planning for effective use of water and land.

Due to the speed and suddenness of flash floods, their brief duration, and the interaction of several natural variables, it is nearly impossible to prevent them; however, we must take action to lessen their negative effects on people and property. By gathering dependable data with enhanced technology and developing forecasting techniques based on modeling and risk assessment expertise, significant efforts are currently being undertaken to raise public knowledge and awareness of flash floods. Every time there is a flash

flood, an assessment is required to determine what went wrong and what can be done better. Similar to how a thorough understanding of the causes that contribute to flash floods as they relate to Port Harcourt would help to mitigate the damage, accurate data on regions of risk will help to tame the danger. The study yielded the following results:

1. The average monthly rainfall in Port Harcourt varied from 136.0 mm to 232.58 mm.
2. The largest monthly rainfall totals were typically seen in July or September; these two months together account for 16% of the annual rainfall totals in each of those years.
3. Rainfall in Port Harcourt is responsible for almost half of the city's flooding.
4. 88% of the time that a study on rainfall was carried out, the total amount of rainfall exceeded 2000 mm.
5. Low permeability causes excessive surface runoff in most of the loamy sand and sandy loam soil samples collected along Nkpolu Road in the Port Harcourt metropolitan area.
6. Ultimately, the Port Harcourt metropolis's Nkpolu Road flood conditions could be instantly communicated to road users via the development of a flash flood warning system.

Recommendations

As long as physical development extends to river channels, flooding, including flash floods, may not always be prevented. Planning, observation, warning, and the application of current development principles are among the flood management techniques used in Nigeria, particularly specifically in Port Harcourt. What is absent are sufficient oversight, effective execution, and a dedication to reevaluating policies to account for population expansion. Instead of taking early, proactive measures before flood events, floods are typically responded to. Since flash floods differ from riverine floods, handling them calls for a distinct strategy. It does not always follow that what works for one will work for the other. In addition to prevention and mitigation strategies, flash flood mitigation must take the area's development requirements into account. In the same way that mitigation measures must be planned and carried out with the current community included, economic growth cannot be sustained if flash floods are permitted to harm or destroy it. Flood mitigation measures need to be inclusive and interactive due to the unusual death rate and destruction caused by flash floods. The first step in mitigating a flash flood is identifying a potential rain event. The last step is informing the public and ensuring that any losses resulting from the mitigation measures implemented are avoided (Grunfest, 1998). Although flash flood mitigation is sometimes viewed as a technological and scientific approach to predicting and warning, it must be comprehensive, addressing all aspects of susceptibility such as land use, planning, allocation, development, channeling, control, and the application of well-considered policies.

The establishment of an appropriate flash flood warning system, in conjunction with community readiness and proper technological advice, will yield the greatest outcomes prior to the flood. While permitting sustainable urban expansion, flash floods must be controlled. The following are some precautions against flash floods.

1. Engineering (structural) Measures: Throughout history, this method of reducing the damage caused by flash floods has been used worldwide. Among other things, this involves planning and building actual buildings to enhance runoff from rainfall, produce water storage, and regulate runoff. A storage reservoir protects the downstream flood plain by storing runoff and allowing for the controlled release of impounded water. Its cost is a drawback, and given the rate of development, it would occasionally need to be enlarged to accommodate growing demands. b) River Basin Management: To intercept and divert floods, shallow dishes are made along river contour lines. In order to minimize damage, this is meant to decrease flow intensity and speed. Groundwater will discover new pathways for the floodwater or runoff to penetrate and seep into. b) Building dikes to prevent flooding: This is an often employed method despite its moderate cost. This prevents the river from flowing beyond its intended course, saving the river valley and surrounding areas from the devastating effects of flooding. d) Drainage facilities: These must have gutters that are in good condition, have the appropriate size and capacity to handle anticipated flooding, and empty into a river or creek. e) Restoring the discharge conditions and raising the rivers' and creeks' ability to convey floodwater by de-silting receiving streams and creeks. This entails removing impediments from the stream and sand and mud from water channels. This ought to be included in a management and regeneration plan for rivers and creeks that is implemented on a regular basis.

2. Non-structural Measures: These are extra, non-engineering steps taken to manage flooding so that development can proceed. a) Raising public awareness about the dangers of obstructing drainage systems and constructing homes and businesses in high-risk regions for flooding. People should stay away from the negative effects that come with occupying and altering flood plains and destroying and modifying wetlands, both in the short and long terms. When there are workable alternatives, they should refrain from directly or indirectly supporting the development of floodplains and new construction in wetlands. b) Planting trees to prevent flooding and limit land usage by enacting land use regulations that take flooding risk into consideration. c) Flood insurance: This enables a property owner to insure against flooding so that the insurance provider will cover any losses brought on by flooding. d) Flood forecasting and warning: These alert the public in advance so they can take the necessary precautions against flooding. Warning has been recognized as a key strategy in lowering susceptibility and exposure since flash floods can arrive quickly, unexpectedly, and with great destructive intensity. Effective warnings require accuracy and prompt action, which is why real-time data and models must be integrated into detection and forecasting systems. e) Sufficient preparation for flooding by relocating items to dry areas, storing food and fuel, and making plans for an escape in case it becomes necessary. f) Flood resilience: Communities naturally adapt to flooding by fortifying themselves against it. Building of flood resistive houses, raising the entrance height of a house, raising the house higher, protecting the house round with impermeable clay sand or cement wall, building public places on high ground, providing high ground for settlement during flood or putting

blockades against expected flood waves from rivers. g) Development Policies: All tiers of government should create and implement development policies that are closely monitored and comprehensively explain the kinds of development that are permitted in particular city regions and those in which development is strictly prohibited. The government is also responsible for removing any structure that obstructs the drainage path or violates state development regulations. The government must find ways to revitalize urban areas and spur new development while linking the goals of urban planning to flood control measures. The authorities at different levels of government must be clearly defined, and there must be a definite process for getting approval or a permit for development. h) Disaster relief and management: A concentrated effort should be made by the government, non-governmental organizations, and public-spirited individuals to reduce the negative effects of flooding on people's health, safety, and welfare. One possible way to achieve this is by including funds in the annual budget and plans for disaster management, which may then be utilized to supply food, clothing, temporary housing, and other necessities in the event of a flood disaster. The government and public-spirited people can help property owners who have had their lives wrecked by flooding by giving them the money they need to start anew. For a limited time, those impacted by flooding may get social security benefits until they have fully recovered. i) Public involvement: The public must be included in all decision-making processes related to flood plain management and wetland protection. They will be more resistant to structural measures as a result, even when they take part in non-structural measures. The public has a responsibility to spread the word about impending disasters and take action to prevent them while also carrying the message themselves. Flood Education in Schools: To ensure that our kids pass on effective flood prevention practices to their parents and others in their immediate vicinity, the government should consciously teach our kids in schools and perhaps even instill these lessons in them. Given that the next generation of leaders will be children, it is appropriate to educate them early on about the threats that floods of all types bring to our civilization and well-being. This will lead to a paradigm change from helping floods to preventing them. The majority of drainage obstructions are the result of youngsters who view the drainages as places to dump trash, either on their own or through the actions of their parents. k) Giving the populace access to sufficient security. Whether it be structural, economic, or social, security is the cornerstone of all development initiatives. Security is feeling safe and protected from the people around you as well as having personnel with weapons to guard a place. Developers won't worry about enclosing their home in the same manner as Port Harcourt's modest structures are, since they are well aware of their level of protection. The city's flood was partially caused by the fencing, or the installation of demarcating and security fences, which significantly impedes the free flow of runoff water from rainfall. Overcrowding prevents water from flowing naturally and does not provide enough space for diversion. As it searches for equilibrium, water accumulates in areas where it cannot flow freely, creating floods.

References

1. Akinyemi T. Stemming the tide of Lagos floods, in: The Guardian. Friday, 1989.
2. Akukwe TI. Determinants of flooding in Port Harcourt metropolis, Nigeria, 2014.
3. Akukwe TI, Ogbodo C. Spatial Analysis of Vulnerability to Flooding in Port Harcourt Metropolis, Nigeria, 2015. SAGE Open Do 1: 10. 75558. Sgo. Sagepub.com.
4. Alexander D. Confronting catastrophe: New perspective on natural disasters. Oxford University Press, 2012.
5. Alasali F, Tawalbeh R, Ghanem Z, Mohammad F, Alghazzawi M. A Sustainable Early Warning System Using Rolling Forecasts Based On Ann And Golden Ratio Optiimization Methods To Accurately Predict Real-Time Water Level And Flash Flood. Sensors,2021;21(13):4598.
6. Ali E. Geographic Information System (GIS): Definition, Development, Applications & Components. Faculty, Department of Geography Ananda Chandra College, Jalpaiguri, 2020. aliershad.geo@gmail.com
7. Ali I, Mario O, Mohamad A, Moustafa S, Hussein C, Maurizio V. Approximate Computing Methods for Embedded Machine Learning. 2018 25th IEEE International Conference on Electronics, Circuits and Systems (ICECS), 2019, 845-848. doi:10.1109/ICECS.2018.8617877. ISBN 978-1-5386-9562-3. S2CID 58670712.
8. Alpaydin E. Introduction to Machine Learning. MIT Press, 2010, 9. ISBN 978-0-262-01243-0.
9. Alpaydin, E. Introduction to Machine Learning. London: The MIT Press. ISBN 978-0- 262-01243-0. Retrieved, 2017.
10. Alpaydin E. Introduction to Machine Learning (Fourth ed.). MIT. pp. xix,2020:1–3:13–18. ISBN 978-0262043793.
11. Amangabara GT, Gobo AE. Factors that influence the flooding of the middle and lower Ntamogba stream catchments, Port Harcourt, Nigeria. Journal of Environmental Hydrology, 2007, 15(17).
12. Angwin J, Larson J, Kirchner L, Mattu S. Machine Bias. Pro Publica, 2016. Retrieved 2018-08-20.
13. Analytics India Magazine. A Beginner's Guide To Machine learning For Embedded Systems, 2021. Retrieved 2022-01-17.
14. Arduino Blog. Announcing the Arduino IoT Cloud Public Beta. 2019-02-06. Retrieved 2020-06- 23.
15. Arduino.cc. Getting Started: FOUNDATION > Introduction. Archived from the original on 2017-08-29. Retrieved 2017-05-23.
16. Arduino.cc. Policy. Retrieved 2013-01-18.
17. Arduino.cc. arduino/Arduino. May 5, 2021
18. Arvind N. Language necessarily contains human biases, and so will machines trained on language corpora. Freedom to Tinker, 2016.